





## PRODUCT INFORMATION: FOR ALL EXTERIOR WOOD

THORNDOWN WOOD PRESERVATIVE is a ready to use, water-based wood preservative, designed to protect new and existing softwood timber without ground and water contact.

It protects timber against brown rot (Gloeophyllum trabeum, Conjophora puteana, Poria placenta) and blue stain fungi (Aureobasidium pullulans spp, Sclerophoma pithyophilla). Made for outside application on wood.



Protects timber against brown rot and blue stain fungi



Use in Class 2 and 3 cf. DS/EN335: 2013. Conforms to EN 113 after EN 84 / EN 73 and EN 152



**Drying time** - quick drying - dry in 1 hour in fine weather conditions (23°C and 60% relative humidity)



Acts as a **primer** 



Overcoat in 6 hours to 4 weeks



Ready to use



Preserves new and existing softwood



For **outside** application on wood



Coverage - treatment rate of 180 to 220 ml/m<sup>2</sup> equalling approximately 5.5 m<sup>2</sup> per litre - giving you 2 coats on planed surfaces, or 1 coat on rough sawn timbers as it soaks in more treatment



**GB-BPR approved wood preservative** Registration Number GB-2013-0783-1-0002



Water-based with low odour



Coats - 2 coats for planed (smooth) timber and one for rough sawn



**Usability** - apply by brush, or roller for DIY. Easy to clean up with water and mild soap



Produces excellent broad spectrum protection against wood destroying & blue stain fungi



Can be used **DIY**, **professional** and **industrial** 



























NICE CANS and more air space above the