





WALL PAINT

PRODUCT INFORMATION: FOR ALL INTERIOR SURFACES

"Thorndown Wall Paint - stunning high-performance eco paint with minimal VOC for indoor use. Beautiful deep colours crafted with strong exterior-grade colour pigments that sit in a water-based durable and dirt resistant coating. Designed using sustainable, recycled and recyclable raw materials where possible. For use on any walls and ceilings, anywhere."

The paint has been developed to be the best interior wall paint on the market, tested and proven to be many times tougher than the competition. With architectural exterior-grade colour pigments that perform at the highest levels in tests, the paint colours stay strong and true for many, many years.

- Stunning, carefully crafted high performance **Eco paint water-based** eco product with **low odour** and **minimal VOC** (Volatile Organic Compounds) at 0.28%
- Sustainable fillers from recycled waste marble and resin from recycled car windscreens
- One wall paint product for any interior application; living rooms, nursery, bathrooms, kitchens, hallways, porches, radiators, doors, frames, wood trims and furniture
- Deep velvety Flat Matt durable finish <3% gloss, covering up to 12m² per litre per coat
- Minimum of prep required and can be easily painted on previously coated surfaces
- Water resistant, micro-porous coating (allows wall to breathe); resin lasts up to 10 years
- **2 coats** recomended for full coverage, with a 3rd deepening and increasing opacity of lighter shades. May require more depending on substrate and colour change from previous coating
- Can **dilute for a mist/primer coat**. Dilute paint by approximately 30% water increasing to 40% water in hot, dry conditions
- Very strong bond with walls but **also coats wood, metal, stone, terracotta**. Specific primers may be required for certain surfaces
- Strong, deep, long-lasting external grade colour pigments with high resistance to UV degradation & colour fade
- Great core **colour range 56** colours in the Wall Paint Colour Collection
- 1800 RAL Classic and RAL Design colours, 2050 NCS colours, 434 British Standard BS318C BS4800 BS5252F and Pantone C colours also available
- Mix colours together easily to create bespoke shades

Can be used on **exterior walls** and **woodwork** such as doors and window frames, and garden timber products from summerhouses and sheds to arbours. Although Thorndown Wall Paint is a high performance paint it's not as durable as our Wood Paint which is specifically engineered for exterior use. The flat matt finish of the Wall Paint makes it easier for algae and dirt to stick to the coating (whereas on a satin sheen coating it tends to slide off) so it will require cleaning and maintenance on a more regular basis



























NICE CANS

For your convenience, our tins have been designed with a wider top for easy painting and more air space above the paint level for easy mixing.







PRODUCT INFORMATION: FOR ALL INTERIOR SURFACES

PREPARATION

Make sure all surfaces are sound, clean and dry. If required fill and sand to a flat surface.

Remove any grease or oils with a soap solution or something like sugar soap for stubborn areas.

Flaking paint and rust should be removed prior to painting. Porous surfaces or fresh plaster should be sealed first with a diluted 'mist' coat, making sure plaster is thoroughly dry before application, otherwise use paint straight from the tin.

If painting onto wood surfaces that may be prone to resin bleed or tanning coming out of the timber, apply 1 or 2 coats of Stain Blocking Primer before painting to avoid paint coatings becoming stained.

DILUTION

For a mist/primer coat, dilute paint by approximately 30% water increasing to 40% water in hot, dry conditions, otherwise use straight from the tin including in sprayers.

APPLICATION

BEST SHAKEN & STIRRED! Mix paint thoroughly before and during. Use a good quality synthetic brush, roller, or sprayer. When coating large areas, cover up to still-wet paint to avoid an uneven patchy coating.

Adheres well to metal radiators and interior woodwork from doors to skirting boards and furniture.

COATS

Two coats for a full, deep coating. Three coats will enhance lighter colours and increase opacity of coating. Please note that due to the flat matt nature of Thorndown Wall Paint, the colour may appear slightly darker than with the satin sheen of Wood Paint.

In fine weather, a single coat dries easily in under an hour. Drying time is extended in cold damp conditions.

CLEANING UP

Use hot or cold water, with or without detergent, on paint-wet equipment. Be very careful not to allow sprayer nozzles to dry out - this will make cleaning them almost impossible!

DISPOSAL

Please, please don't throw away unused or dried paint or preserver into drains or watercourses. Most local authorities have free facilities for disposing of paint and coatings. Tins are fully recyclable but remember to make sure they're clean. All packaging is fully recyclable.

Paint will keep for approx. 2 years or more in a sealed tin stored out of freezing or extremely high temperatures. Mix well before use with a paint stirrer or hand blender.

You'll paint up to 12m² of a flat surface (one coat) with one litre. So each paint can will do approximately:

150 ml 1.8m²

750 ml 9.0m²

2.5 I

30m²

























